



APPLICATION

For conventional machine tools.

TYPE

Clamping system mechanical without power transmitter, manually operated.

CUSTOMER BENEFITS

- Optimal price/performance ratio
- Entire clamping range can be bridged over by turning the handcrank
- Spindle is protected from dirt and chips
- Extensive assortment of jaws

TECHNICAL FEATURES

- Made of special cast iron for versatile use
- Long guidance of moving jaw
- Force transfer by means of threaded spindle
- With normal jaws SGN and handcrank
- Use on rotary plate with graduation

A11 **RS** with SGN normal jaws and hand crank

Item no.	128031	128032	128033	128034	111648
Size	1	2	3	4	5
Jaw width A mm	92	113	135	160	200
B mm	85	105	125	145	185
C mm	31.6	31.6	39.6	49.6	62.6
D mm	362	423	510	575	675
F mm	260	300	365	410	460
G mm	48	58	64	70	82
H mm	50	55	70	80	90
J mm	174	200	242	273	322
K mm	160	160	200	240	280
O mm	115	125	155	175	200
P mm	60	60	70	80	118
Q mm	13	13	13	17	21
R mm	14	14	14	18	22
S mm	120	120	146	184.5	210
Y mm	12	12	16	16	20
a mm	63	63	80	100	125
b mm	13.6	13.6	15.6	19.6	24.6
c	M6	M6	M8	M8	M10
Clamping force kN	18	25	35	45	55
Weight kg	12	13.5	25	40	65

