



## Take-up housing units MSTU25-XL (Series MSTU)

sheet steel housing, radial insert ball bearing with eccentric locking collar, P seals, with relubrication facility

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	25 mm
L	203,2 mm
H	104,8 mm
U	33,8 mm
A	19 mm
A <sub>2</sub>	10,3 mm
B <sub>1</sub>	31 mm
d <sub>3 max</sub>	37,5 mm
J	80,2 mm
S	2 mm

m	0,58 kg	Mass
C <sub>0r G</sub>	3900 N	Load carrying capacity of housing, radial
C <sub>r</sub>	14900 N	Basic dynamic load rating, radial
C <sub>0r</sub>	7800 N	Basic static load rating, radial
	GEH52-MSTU	Designation of housing
	RAE25-XL-NPP-B	Designation of bearing



