

# FatMax®

0-89-858  
0-89-859



0-89-875



0-89-871  
0-89-872



0-89-869  
0-89-870



0-89-874



- Two-component handle
- DIN / ASO / ANSI compliant
- Hand ground, induction hardened blade for long life and high quality accuracy

- Heat treated high chrome steel forging for long life and durability
- Bi-material handle with secure grip grooving

0-89-866  
0-89-867  
0-89-868



0-89-873



0-89-860  
0-89-861  
0-89-862



0-84-496



0-84-495



| STANLEY  | i                                     |   |    |               |
|----------|---------------------------------------|---|----|---------------|
| 0-89-866 | combination plier, 150 mm             | X | 4  | 3253560898663 |
| 0-89-867 | combination plier, 180 mm             | X | 4  | 3253560898670 |
| 0-89-868 | combination plier, 200 mm             | X | 4  | 3253560898687 |
| 0-89-860 | angled diagonal cutting plier, 160 mm | X | 4  | 3253560898601 |
| 0-89-861 | angled diagonal cutting plier, 180 mm | X | 4  | 3253560898618 |
| 0-89-862 | angled diagonal cutting plier, 250 mm | X | 4  | 3253560898625 |
| 0-89-858 | diagonal cutting plier, 160 mm        | X | 4  | 3253560898588 |
| 0-89-859 | diagonal cutting plier, 200 mm        | X | 4  | 3253560898595 |
| 0-89-875 | end cutter, 160 mm                    | X | 4  | 3253560898755 |
| 0-89-873 | wire stripper, 160 mm                 | X | 4  | 3253560898731 |
| 0-89-869 | long nose plier, 160 mm               | X | 4  | 3253560898694 |
| 0-89-870 | long nose plier, 200 mm               | X | 4  | 3253560898700 |
| 0-89-871 | bent long nose plier, 150 mm          | X | 4  | 3253560898717 |
| 0-89-872 | bent long nose plier, 200 mm          | X | 4  | 3253560898724 |
| 0-89-874 | cable cutter, 200 mm                  | X | 4  | 3253560898748 |
| 0-84-613 | groove joint 200 m                    | X | 12 | 3253560846138 |
| 0-84-614 | groove joint 300 mm                   | X | 12 | 3253560846145 |
| 0-84-615 | slip slot 150 mm                      | X | 12 | 3253560846152 |
| 0-84-629 | slip joint 200 mm                     | X | 12 | 3253560846299 |
| 0-84-495 | flat, 150 mm                          | X | 4  | 3253560844950 |
| 0-84-496 | round, 165 mm                         | X | 4  | 3253560844967 |