

# CAMPUS

Surface LED module



### Features:

Surface module with opal diffuser, ideal for schools and corridors

Available in 2 sizes and 2 outputs

Gear options including DALI and emergency available

CRI: Ra>80

Up to 130 lumens per Watt efficacy

50,000 hours lifetime (L70/B50)

### Construction:

Steel body with BESA fixings and rear or end cable-entry

White (RAL 9016)

Opal polycarbonate diffuser

Supplied as standard with neutral white (4000K) LED

### Options:

D - Dimmable DALI

M3 - 3 hours integrated emergency

A3 - Emergency self test

D3 - DALI self test

# CAMPUS

Surface LED module

### Order Codes


All dimensions are in millimetres

Order code	Description	Lumens (lm)	Total power (W)	Efficacy (lm/W)	Weight (kg)
CMP4390NW	33W - 4000K	3900	33	118	1.70
CMP5690NW	53W - 4000K	6900	53	130	2.00

### Dimensions

All dimensions are in millimetres

Order code	A	B	C
CMP4390NW	1203	150	70
CMP5690NW	1503	150	70



### Installation instructions:

Surface fix via rear mounting holes and wired via 3-pole terminal block

### To specify:

LED surface module as per Tamlite CAMPUS range

Please Note: Order codes listed are for standard (non-emergency) versions only. For all other gear options, please contact Tamlite Lighting.