

DESCRIPTION

Ideal for sealing tar, bitumen and creosoted surfaces and to prevent bleeding through in subsequently applied oil based paints. Can also be used as a quick drying white line paint.

RECOMMENDED USES



Primer and sealer for timber, wood composites, plaster, cement and brickwork. Seals tar, bitumen, creosoted areas.

SPECIAL PROPERTIES

Rapid drying. Can also be used as a quick drying white line paint.

COLOUR RANGE

Brilliant White.

FINISH

Matt.

VOLUME SOLID

45%.

COVERAGE



Johnstone's Quick Dry Primer Sealer will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 10 minutes.
Recoat after 30 minutes.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

CLEANER

Mineralised Methylated Spirit.

VOC CONTENT

HIGH VOC CONTENT 25–50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 600g/l (2007) / 500g/l (2010).
This product contains max 500g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 25µm.

SIZE

2.5 Litre.

PREPARATION

All surfaces should be clean, dry and free from oil, grease and loose and flaking material.

APPLICATION



Stir well before use. Suitable for application by brush or roller. Apply a full coat, freely and smoothly with the minimum of brushwork. If a second coat is required, this can be applied after approximately 30 minutes. Avoid over-brushing.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with Mineralised Methylated Spirit. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT UN 1263.
- HIGHLY FLAMMABLE.
- Keep container tightly closed in a cool well ventilated area.
- Keep away from sources of ignition – No smoking.
- Use only in well ventilated areas.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- When applying to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air fed respiratory protective equipment.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

