



- Quick and easy installation
- Highlight hazardous feature
- Marking according to DIN 4844
- Available in 3 formats to suit most conditions
- Permanent adhesive

H & S Statement:

Health & Safety Regulations state that permanent obstructions or danger zones should be marked yellow and black, and that temporary obstructions should be marked in red and white.

Floor marking and Repair

Hazard Warning Tape
Self-adhesive

Accidents often occur when hazards are not clearly marked. Our range of Hazard Warning tapes provides the ideal solution for most common situations. Quick and easy to install our self-adhesive tapes adhere to smooth, dust and grease free surfaces and can be removed without leaving a residue from most surfaces.



Non-reflective Hazard Warning Tape

Quickly and easily applied this low cost self-adhesive hazard warning tape is ideal for highlighting indoor hazards in most daylight and artificial light conditions.



Reflective Hazard Warning Tape

This high quality, UV resistant and long lasting tape provides excellent visual warning both indoors and outdoors of hazards in a wide range of lighting conditions.



Luminescent Hazard Warning Tapes

An extremely high quality Hazard Warning Tape which has a long lasting luminous effect in all light conditions and especially in difficult situations such as darkness and smoke.

Description	Size (mm x m)	Colour	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
Non reflecting Roll –right-hand direction	60 mm x 66 m	red/white	0,5	420.11.054	1 / 2 days
		black/yellow		420.11.965	
Retro reflecting 2 roll pack (1 right-hand-, 1 left-hand direction)	50 mm x 25 m	red/white	1	420.11.114	5 / 10 days
		black/yellow		420.12.062	
Long lasting Luminous effect 2 roll pack (1 right-hand-, 1 left-hand direction)	50 mm x 16 m	red/lux-white	0,5	420.18.167	
	100 mm x 16 m		1	420.19.444	
	50 mm x 16 m	black/lux-white	0,5	420.13.232	
	100 mm x 16 m		1	420.16.818	
Long lasting Luminous effect 1 roll	25 mm x 25 m	single colour luminous (lux-white)	0,2	420.18.600	
	50 mm x 25 m		0,4	420.15.285	