




Technical data

4T-L319249

Single row tapered roller bearings

Mounted cone, sheet metal cage

Visual(s)



Product definition

d	95.25 mm
B	21.43 mm
d1	113.5 mm
e	0.35
Y2	1.72
Y0	0.95
Brand	NTN

Product performance

Dynamic load, C	81 kN
Rating life coefficient, A2	1.4
Static load, C0	147 kN
Fatigue limit load, Cu	17.3 kN
Nlim (oil)	3,300 Tr/min
Nlim (grease)	2,500 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	15.2 Hz
Characteristic outer ring frequency, BPF0	16.85 Hz
Characteristic inner ring frequency, BPFI	19.15 Hz

Abutment dimensions

ra max

1.5 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table