


# ISO cylinder DSBC-50-100-D3-PPSA-N3

Part number: 3659499

FESTO



 General operating condition

## Data sheet

| Feature                                                      | Value                                                                                      |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Stroke                                                       | 100 mm                                                                                     |
| Piston diameter                                              | 50 mm                                                                                      |
| Piston rod thread                                            | M16x1.5                                                                                    |
| Cushioning                                                   | Self-adjusting pneumatic end-position cushioning                                           |
| Mounting position                                            | optional                                                                                   |
| Conforms to standard                                         | ISO 15552                                                                                  |
| Piston-rod end                                               | Male thread                                                                                |
| Design                                                       | Piston<br>Piston rod<br>Profile barrel                                                     |
| Position detection                                           | Via proximity switch                                                                       |
| Symbol                                                       | 00992970                                                                                   |
| Variants                                                     | Piston rod at one end                                                                      |
| Operating pressure                                           | 0.04 MPa ... 1.2 MPa                                                                       |
| Operating pressure                                           | 0.4 bar ... 12 bar                                                                         |
| Mode of operation                                            | Double-acting                                                                              |
| Operating medium                                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                               | 2 - Moderate corrosion stress                                                              |
| LABS (PWIS) conformity                                       | VDMA24364-B1/B2-L                                                                          |
| Ambient temperature                                          | -20 °C ... 80 °C                                                                           |
| Impact energy in end positions                               | 1 J                                                                                        |
| Cushioning length                                            | 22 mm                                                                                      |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke  | 990 N                                                                                      |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 1178 N                                                                                     |
| Moving mass for 0 mm stroke                                  | 365 g                                                                                      |
| Additional moving mass per 10 mm stroke                      | 25 g                                                                                       |
| Basic weight for 0 mm stroke                                 | 1216 g                                                                                     |
| Additional weight per 10 mm stroke                           | 78 g                                                                                       |
| Type of mounting                                             | Either:<br>Via female thread<br>With accessories                                           |
| Pneumatic connection                                         | G1/4                                                                                       |
| Note on materials                                            | RoHS-compliant                                                                             |
| Material cover                                               | Die-cast aluminium, coated                                                                 |
| Material piston seal                                         | TPE-U(PU)                                                                                  |

| Feature                    | Value                                   |
|----------------------------|-----------------------------------------|
| Material piston            | Wrought aluminium alloy                 |
| Material piston rod        | High-alloy steel                        |
| Material piston rod wiper  | TPE-U(PU)                               |
| Buffer seal material       | TPE-U(PU)                               |
| Cushioning piston material | POM                                     |
| Material cylinder barrel   | Smooth-anodised wrought aluminium alloy |
| Material nut               | Galvanised steel                        |
| Material rod wiper         | TPE-E                                   |
| Material bearing           | Metal polymer compound                  |
| Material collar screws     | Galvanised steel                        |