





















Data

| | |
|--------------------------|------------------|
| Working temperature: | -20 °C to +70 °C |
| Working pressure: | max 10 bar |
| Flow (acc. to ISO 6358) | |
| C: | 0,9 Nl/s, bar |
| Qn (P1=6 bar, Δp=1 bar): | 3,6 l/s |
| Qmax: | 6,3 l/s |
| Cv: | 0,21 |

| | Symbol | Actuator | Return | Mounting | Changeover force at 6 bar | Weight kg | Order code |
|---|---|---|-----------------|--|---------------------------|-----------|-------------------|
|  |  | Push-button Red | Spring | Panel mounted | 34,5 N | 0,46 | VA15-HIS4 |
|  |  | Hand lever Held in two positions | Hand lever | Panel mounted | 9 N | 0,63 | VA15-HB24 |
|  | | | | Side mounted | 9 N | 0,45 | VA15-HB2 |
|  |  | Hand lever Held in three positions | Hand lever | Panel mounted Closed centre position | 9 N | 0,63 | VA15-HB34 |
|  |  | Hand lever Held in three positions | Hand lever | Panel mounted Exhausted centre position | 9 N | 0,63 | VA15-XHB34 |
|  |  | Hand lever Three positions self-centring | Hand lever | Panel mounted Closed centre position | 9 N | 0,63 | VA15-HC4 |
|  |  | Hand lever Three positions self-centring | Hand lever | Panel mounted Exhausted centre position | 9 N | 0,63 | VA15-XHC4 |
|  |  | Knob Red Two positions | Knob | Panel mounted | 5 N | 0,58 | VA15-KL24 |
|  | | | | Side mounted | 5 N | 0,42 | VA15-KL2 |
|  |  | Knob Red | Spring | Panel mounted | 34,5 N | 0,60 | VA15-KS4 |
|  |  | Knob Red Two positions | Knob/Air signal | Panel mounted | 8 N* | 0,61 | VA15-KL2A4 |

*Without signal pressure. Signal pressure min 3 bar at 6 bar supply pressure.