




Technical datasheet

NU2314EG1C3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Visual(s)



Product definition

d	70 mm
D	150 mm
B	51 mm
E	130 mm
F	89 mm
rs min	2.1 mm
r1s min	2.1 mm
Radial clearance class	C3
Mass (without HJ ring)	3.98 kg
Brand	NTN

Product performance

Dynamic load, C	223 kN
Static load, C0	262 kN
Fatigue limit load, Cu	31.1 kN
Nlim (oil)	4,400 rpm
Nlim (grease)	3,800 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.32 Hz
Characteristic outer ring frequency, BPF0	5.32 Hz
Characteristic inner ring frequency, BPF1	7.68 Hz

Abutment dimensions

da min	81 mm
da max	87 mm
db min	92 mm
Da max	139 mm
ra max	2 mm
r1a max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$