


## **The Timken Company** 4500 Mt Pleasant St. NW

N. Canton, OH 44720 **Phone:** (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number VCJT 13/16, Fafnir® Two-Bolt Flanged Units Eccentric Locking Collar






## <u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u>


pecifications						
Shaft Size d	1 3/16 in 30.2 mm					
Bearing Type	Ball Bearing					
Bearing Number	GRA103RRB					
Dimension E	1.854 in 47.1 mm					
Inside Ring Outside Diameter	1.720 in 43.7 mm					
Series	Standard					
Weight	2.262 lb 1.026 Kg					
Seal Type	Molded Shroud					
Housing Construction	Two-Bolt Flange					

VCJT13/16

Dimensions -					
Housing Width A	29.9 mm 1.177 in				
Total Length H	141.3 mm 5.563 in				
Total Height L	79.4 mm 3.126 in				
Bolt Hole Spacing J	116.7 mm 4.594 in				
Bolt Hole Size N	11.5 mm 0.453 in				
Flange Thickness A1	11.9 mm 0.469 in				
Center of Bearing from House End A2	20.1 mm 0.791 in				
Inside Ring Width B	35.7 mm 1.406 in				
Center of Bearing from Bear End S	ing 20.1 mm 0.791 in				

Bas	sic Load Ratings		-
	Static Load Rating	2530 lbf 11300 N	
	Dynamic Load Rating	4850 lbf 21600 N	





	Bearing Number	GRA103RRB				[a=15.25] / 25.85.25 =15.\52•	
	Load Ratings - C <sub>r</sub>	4850	lbf	21600	N		
	Load Ratings - C <sub>0r</sub>	2530	lbf	11300	N		F
	Weight	2.262	lb	1.026	kg	THE TIMKEN COMPANY	
						NORTH CANTON, OHIO USA	
e to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors.							

VCJT 1 3/16
Fafnir® Two-Bolt Flanged Units Eccentric Locking
Collar

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for erro omissions or for any other reason.

FOR DISCUSSION ONLY