

Bevel brushes, knotted wire



Knotted bevel brush, industrial quality, for use on angle grinders.

- Aggressive cleaning performance
- Long service life
- Combines the best properties of a cup brush with those of a wheel brush
- Workpieces with large areas and difficult to access places can be treated perfectly
- TÜV-Süd certified (safety tested, production monitored)

Applications : Deburring, removal of rust, paint, slag, silicates and blue discolouration on complex workpieces.

Filament	Diameter	max. RPM	Ø Bore	Thread Size	Trim Length	Ø Filament	Fill Material Grade	Knot Count	Face Width	Order no.	PU
T2 Oil tempered	100	12500	16.00		22	0.5	T2 Oil tempered	18	13.00	1602622151	10
T2 Oil tempered	115	12500	16.00		20	0.5	T2 Oil tempered	18	15.00	1602632151	10
T2 Oil tempered	100	12500		M10X1,25	22	0.5	T2 Oil tempered	18	13.00	2352622151	10
1.4310	100	12500		M10X1,25	22	0.5	1.4310	18	13.00	2352622351	5
T2 Oil tempered	125	12500		M14	23	0.5	T2 Oil tempered	24	15.00	2902632151	10
T2 Oil tempered	125	12500		M14	23	0.35	T2 Oil tempered	24	15.00	3602632131	10
1.4310	125	12500		M14	23	0.35	1.4310	24	15.00	3602632331	10
1.4310	125	12500		M14	23	0.5	1.4310	24	15.00	3602632351	10
	100	12500		M10X1,25	22	0.35		18	13.00	4802622131	10
1.4310	100	12500		M10X1,25	22	0.35	1.4310	18	13.00	4802622331	5
T2 Oil tempered	100	12500		M14	22	0.35	T2 Oil tempered	18	13.00	0002622131	10
T2 Oil tempered	100	12500		M14	22	0.5	T2 Oil tempered	18	13.00	0002622151	10
1.4310	100	12500		M14	22	0.35	1.4310	18	13.00	0002622331	5
1.4310	100	12500		M14	22	0.5	1.4310	18	13.00	0002622351	5
T2 Oil tempered	100	12500		M14	22	0.35	T2 Oil tempered	22	13.00	0002623131	10
T2 Oil tempered	100	12500		M14	22	0.5	T2 Oil tempered	22	13.00	0002623151	10
T2 Oil tempered	115	12500		M14	20	0.35	T2 Oil tempered	18	15.00	0002632131	10
T2 Oil tempered	115	12500		M14	20	0.5	T2 Oil tempered	18	15.00	0002632151	10
1.4310	115	12500		M14	20	0.35	1.4310	18	15.00	0002632331	5
1.4310	115	12500		M14	20	0.5	1.4310	18	15.00	0002632351	5
T2 Oil tempered	100	12500		M10X1,5	22	0.35	T2 Oil tempered	18	13.00	0102622131	10
T2 Oil tempered	100	12500		M10X1,5	22	0.5	T2 Oil tempered	18	13.00	0102622151	10
1.4310	100	12500		M10X1,5	22	0.35	1.4310	18	13.00	0102622331	5
1.4310	100	12500		M10X1,5	22	0.5	1.4310	18	13.00	0102622351	5
1.4401	100	12500		M14	22	0.5	1.4401	18	13.00	0442622351	5
1.4401	115	12500		M14	20	0.5	1.4401	18	15.00	0442632351	5
T2 Oil tempered	115	12500		5/8"	20	0.35	T2 Oil tempered	18	15.00	0802632131	10
T2 Oil tempered	115	12500		5/8"	20	0.5	T2 Oil tempered	18	15.00	0802632151	10
1.4310	115	12500		5/8"	20	0.35	1.4310	18	15.00	0802632331	5
1.4310	125	12500		5/8"	20	0.5	1.4310	18	15.00	0802632351	5