

# Latex exam gloves, offering robust personal protection and secure grip

- Tough, durable latex: Designed for demanding jobs
- Soft, smooth feel: Ensures a comfortable feel and easy donning
- Enhanced finger thickness: Protects against tears and snags



# **Industries**

- Automotive
- Automotive Aftermarket
- Life Sciences
- Machinery and Equipment

# **Recommended For**

- Inspection, selecting, checking parts
- General Purpose Auto Aftermarket
- Oil, fluids and filter change
- Engine transmission and repair
- Tire rotation & changes
- Maintaining lab furniture and equipment
- Sample taking and processing
- Raw material sample collection
- Inspection (picking, checking and marking)





## **TECHNICAL DATA SHEET**

|  | Product Information  |
|--|--|
| External Glove Surface                 | Textured Fingers   |
| Audit Standards                        | ISO 13485, ISO 9001  |
| Product Certification                  | Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks   |
| Packaging Overview                     | 100 gloves per dispenser<br>10 dispensers per case<br>1000 gloves per case   |
| Storage Instructions                   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.   |
| Country Of Origin                      | Malaysia   |
| Product Segmentation                   | Robust   |
| Antistatic                             | No   |
| Vulcanization Chemical<br>Accelerators | <ul> <li>Zinc Dibutyldithiocarbamate (ZDBC)</li> <li>Zinc Diethyldithiocarbamate (ZDEC)</li> <li>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</li> </ul> |

#### **PHYSICAL PROPERTIES**

|   | Typical             | Values      | Testing Method               |  |
|---|---------------------|-------------|------------------------------|--|
| Length (mm/inches)                      | 245 / 9.6           |             | ASTM D3767,ASTM D6977,EN 420 |  |
| Freedom from Holes (Inspection level I) | 1.5 AQL             |             | ASTM D5151,EN 455-1          |  |
| Palm Thickness (mm/mils)                | 0.16 / 6.3          |             | ASTM D3767,EN 420            |  |
| Finger Thickness (mm/mils)              | 0.20 / 7.9          |             | ASTM D3767,EN 420            |  |
|   | <b>BEFORE AGING</b> | AFTER AGING |                              |  |
| Ultimate Tensile Strength (MPa)         | ≥ 18                | ≥ 21        | ASTM D412 & D573             |  |
| Elongation at Break (%)                 | ≥ 750               | ≥ 600       | ASTM D412                    |  |
| Force at break (N)                      | ≥ 6                 | ≥6          | EN 455-2                     |  |

## **ORDERING INFORMATION**

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 63864060     | 63864070    | 63864080    | 63864090    | 63864100      |

#### **Performance Standards and Regulatory Compliance**



















# For additional information visit us at www.ansell.com, or call us at

#### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

## Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699

## North America Region

Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

# Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

#### Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

#### Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2022 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

