




Technical datasheet

NU2217ET2XC3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, polyamide cage

Visual(s)



Product definition

d	85 mm
D	150 mm
B	36 mm
E	136.5 mm
F	100.5 mm
rs min	2 mm
r1s min	2 mm
Radial clearance class	C3
Mass (without HJ ring)	2.54 kg
Brand	NTN

Product performance

Dynamic load, C	217 kN
Static load, C0	279 kN
Fatigue limit load, Cu	32.4 kN
Nlim (oil)	4,300 rpm
Nlim (grease)	3,700 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.43 Hz
Characteristic outer ring frequency, BPF0	7.21 Hz
Characteristic inner ring frequency, BPF1	9.79 Hz

Abutment dimensions

da min	94 mm
da max	99 mm
db min	104 mm
Da max	141 mm
ra max	2 mm
r1a max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$