


The Timken Company 4500 Mt Pleasant St. NW

N. Canton, OH 44720 **Phone:** (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number VCJT 5/8, Fafnir® Two-Bolt Flanged Units Eccentric Locking Collar







<u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u>

Specifications					
Shaft Size d	5/8 in 15.9 mm				
Bearing Type	Ball Bearing				
Bearing Number	GRA010RRB				
Dimension E	1.547 in 39.3 mm				
Inside Ring Outside Diameter	1.106 in 28.1 mm				
Series	Standard				
Weight	1.301 lb 0.590 Kg				
Seal Type	Molded Shroud				
Housing Construction	Two-Bolt Flange				

Dimensions					
	Housing Width A	23.6 mm 0.929 in			
	Total Length H	98.4 mm 3.874 in			
	Total Height L	53.9 mm 2.122 in			
	Bolt Hole Spacing J	76.20 mm 3.000 in			
	Bolt Hole Size N	10.7 mm 0.421 in			
	Flange Thickness A1	10.3 mm 0.406 in			
	Center of Bearing from Housing End A2	17.1 mm 0.673 in			
	Inside Ring Width B	28.6 mm 1.126 in			
	Center of Bearing from Bearing End S	17.1 mm 0.673 in			

Bas	sic Load Ratings		-
	Static Load Rating	1070 lbf 4700 N	
	Dynamic Load Rating	2380 lbf 10700 N	





	Bearing Number	GRA010RRB			┎╖┼╎╎╱┼ <i>╬</i> ╱┼╖┼\┼		
	Load Ratings - C _r	2380	lbf	10700	N		
	Load Ratings - C _{0r}	1070	lbf	4700	N		
	Weight	1.301	lb	0.59	kg	THE TIMKEN COMPANY	
						NORTH CANTON, OHIO USA	
to ensure the accuracy of the information contained in this writing, but no liability is accented for errors							

VCJT 5/8
Fafnir® Two-Bolt Flanged Units Eccentric Locking
Collar

FOR DISCUSSION ONLY

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for erro omissions or for any other reason.