


RED Tube end reducer


EO 24° DKO swivel / EO 24° cone end



Series 2) 3) 4)	D1	D2	D3	L1	L2	L3	S1	S2	S3	Weight g/1 piece	Order code*	PN (bar) ¹⁾		
												CF	A3C	71
L/LL	06	04	2.5	28.5	24.5	34.0	9	14	10	17	RED06L/04LLOMD	100	100	100
L	08	06	4.0	30.5	23.5	38.0	12	17	14	29	RED08/06LOMD	500	315	315
L	10	06	4.0	32.0	25.0	40.0	14	19	14	36	RED10/06LOMD	500	315	315
L	10	08	6.0	32.0	25.0	40.0	14	19	17	38	RED10/08LOMD	500	315	315
L	12	06	4.0	32.0	25.0	40.0	17	22	14	49	RED12/06LOMD	400	315	315
L	12	08	6.0	32.0	25.0	40.0	17	22	17	49	RED12/08LOMD	400	315	315
L	12	10	8.0	33.0	26.0	41.0	17	22	19	51	RED12/10LOMD	400	315	315
L	15	06	4.0	35.5	28.5	43.0	19	27	14	81	RED15/06LOMD	400	315	315
L	15	08	6.0	35.5	28.5	43.0	19	27	17	85	RED15/08LOMD	400	315	315
L	15	10	8.0	36.5	29.5	44.0	19	27	19	83	RED15/10LOMD	400	315	315
L	15	12	10.0	36.5	29.5	44.0	19	27	22	83	RED15/12LOMD	400	315	315
L	18	06	4.0	35.0	28.0	43.0	24	32	14	109	RED18/06LOMD	400	315	315
L	18	08	6.0	35.0	28.0	43.0	24	32	17	111	RED18/08LOMD	400	315	315
L	18	10	8.0	36.0	29.0	44.0	24	32	19	110	RED18/10LOMD	400	315	315
L	18	12	10.0	36.0	29.0	44.0	24	32	22	110	RED18/12LOMD	400	315	315
L	18	15	12.0	37.0	30.0	45.0	24	32	27	115	RED18/15LOMD	400	315	315
L/S	18	16	12.0	40.0	31.5	49.5	27	32	30	138	RED18L/16SOMD	400	315	315
L	22	06	4.0	39.0	32.0	47.0	27	36	14	158	RED22/06LOMD	250	160	160
L	22	08	6.0	39.0	32.0	47.0	27	36	17	158	RED22/08LOMD	250	160	160
L	22	10	8.0	40.0	33.0	48.0	27	36	19	159	RED22/10LOMD	250	160	160
L	22	12	10.0	40.0	33.0	48.0	27	36	22	157	RED22/12LOMD	250	160	160
L	22	15	12.0	41.0	34.0	49.0	27	36	27	164	RED22/15LOMD	250	160	160
L/S	22	16	12.0	43.0	34.5	52.5	27	36	30	173	RED22L/16SOMD	250	160	160
L	22	18	15.0	41.0	33.5	50.0	27	36	32	167	RED22/18LOMD	250	160	160
L/S	22	20	16.0	45.0	34.5	56.0	32	36	36	203	RED22L/20SOMD	250	160	160
L	28	06	4.0	41.0	34.0	49.0	32	41	14	219	RED28/06LOMD	250	160	160
L	28	08	6.0	41.0	34.0	49.0	32	41	17	221	RED28/08LOMD	250	160	160
L	28	10	8.0	42.0	35.0	50.0	32	41	19	213	RED28/10LOMD	250	160	160
L	28	12	10.0	42.0	35.0	50.0	32	41	22	213	RED28/12LOMD	250	160	160
L	28	15	12.0	43.0	36.0	51.0	32	41	27	218	RED28/15LOMD	250	160	160
L/S	28	16	12.0	45.0	36.5	54.5	32	41	30	227	RED28L/16SOMD	250	160	160
L	28	18	15.0	43.0	35.5	52.0	32	41	32	220	RED28/18LOMD	250	160	160
L	28	22	19.0	45.0	37.5	54.0	32	41	36	222	RED28/22LOMD	250	160	160
L/S	28	25	20.0	50.0	38.0	62.0	41	41	46	300	RED28L/25SOMD	250	160	160
L	35	06	4.0	44.0	37.0	52.0	41	50	14	318	RED35/06LOMD	250	160	160
L	35	08	6.0	44.0	37.0	52.0	41	50	17	318	RED35/08LOMD	250	160	160
L	35	10	8.0	45.0	38.0	53.0	41	50	19	318	RED35/10LOMD	250	160	160
L	35	12	10.0	45.0	38.0	53.0	41	50	22	324	RED35/12LOMD	250	160	160
L	35	15	12.0	46.0	39.0	54.0	41	50	27	328	RED35/15LOMD	250	160	160
L	35	18	15.0	46.0	38.5	55.0	41	50	32	328	RED35/18LOMD	250	160	160
L	35	22	19.0	48.0	40.5	57.0	41	50	36	331	RED35/22LOMD	250	160	160

RED Tube end reducer

EO 24° DKO swivel / EO 24° cone end



Series 2) 3) 4)	D1	D2	D3	L1	L2	L3	S1	S2	S3	Weight g/1 piece	Order code*	PN (bar) ¹⁾		
												CF	A3C	71
L/S	35	25	20.0	52.0	40.0	64.0	41	50	46	366	RED35L/25SOMD	250	160	160
L	35	28	24.0	48.0	40.5	57.0	41	50	41	327	RED35/28LOMD	250	160	160
L/S	35	30	25.0	55.0	41.5	68.0	46	50	50	435	RED35L/30SOMD	250	160	160
L	42	10	8.0	48.5	41.5	56.0	50	60	19	537	RED42/10LOMD	250	160	160
L	42	12	10.0	48.5	41.5	56.0	50	60	22	538	RED42/12LOMD	250	160	160
L	42	15	12.0	49.5	42.5	58.0	50	60	27	534	RED42/15LOMD	250	160	160
L	42	18	15.0	49.5	42.0	58.0	50	60	32	544	RED42/18LOMD	250	160	160
L	42	22	19.0	51.5	44.0	60.0	50	60	36	543	RED42/22LOMD	250	160	160
L	42	28	24.0	51.5	44.0	61.0	50	60	41	539	RED42/28LOMD	250	160	160
L/S	42	30	25.0	57.5	44.0	70.5	50	60	50	588	RED42L/30SOMD	250	160	160
L	42	35	30.0	53.5	43.0	65.0	50	60	50	541	RED42/35LOMD	250	160	160
L/S	42	38	32.0	61.5	45.5	76.0	55	60	60	701	RED42L/38SOMD	250	160	160

¹⁾ Pressure shown = item deliverable

²⁾ LL = very light series; ³⁾ L = light series; ⁴⁾ S = heavy series

PN (bar) = PN (MPa)
10


Delivery without nut and ring. Information on ordering complete fittings or alternative sealing materials see page I7.

Order code suffixes			
Material	Suffix surface and material	Example	Standard sealing material (no additional. suffix needed)
Steel, zinc plated, chrome ⁶ -free	CF	RED18/15LOMDCF	NBR
Steel, zinc yellow plated	A3C	RED18/15LOMDA3C	NBR
Stainless Steel	71	RED18/15LOMD71	VIT

*Please add the **suffixes** below according to the material/surface required.

RED Tube end reducer


EO 24° DKO swivel / EO 24° cone end



Series 3) 4)	D1	D2	D3	L1	L2	L3	S1	S2	S3	Weight g/1 piece	Order code*	PN (bar) ¹⁾		
												CF	A3C	71
S	08	06	4	34.0	27.0	42	14	19	17	42	RED08/06SOMD	800	630	630
S	10	06	4	34.5	27.5	42	17	22	17	55	RED10/06SOMD	800	630	630
S	10	08	5	34.5	27.5	42	17	22	19	58	RED10/08SOMD	800	630	630
S	12	06	4	36.0	29.0	44	17	24	17	66	RED12/06SOMD	630	630	630
S	12	08	5	36.0	29.0	44	17	24	19	68	RED12/08SOMD	630	630	630
S	12	10	7	37.0	29.5	46	19	24	22	75	RED12/10SOMD	630	630	630
S	14	06	4	38.5	31.5	46	19	27	17	88	RED14/06SOMD	630	630	630
S	14	08	5	38.5	31.5	46	19	27	19	90	RED14/08SOMD	630	630	630
S	14	10	7	38.5	31.0	47	19	27	22	91	RED14/10SOMD	630	630	630
S	14	12	8	38.5	31.0	47	22	27	24	100	RED14/12SOMD	630	630	630
S	16	06	4	39.0	32.0	47	22	30	17	112	RED16/06SOMD	630	400	400
S	16	08	5	39.0	32.0	47	22	30	19	114	RED16/08SOMD	630	400	400
S	16	10	7	39.0	31.5	48	22	30	22	115	RED16/10SOMD	630	400	400
S	16	12	8	39.0	31.5	48	22	30	24	118	RED16/12SOMD	630	400	400
S	16	14	10	41.0	33.0	51	24	30	27	128	RED16/14SOMD	630	400	400
S/L	16	15	11	39.0	32.0	47	24	30	27	120	RED16S/15LOMD	400	315	315
S	20	06	4	43.0	36.0	51	27	36	17	172	RED20/06SOMD	420	400	400
S	20	08	5	43.0	36.0	51	27	36	19	174	RED20/08SOMD	420	400	400
S	20	10	7	43.0	35.5	52	27	36	22	174	RED20/10SOMD	420	400	400
S	20	12	8	43.0	35.5	52	27	36	24	177	RED20/12SOMD	420	400	400
S	20	14	10	45.0	37.0	55	27	36	27	182	RED20/14SOMD	420	400	400
S/L	20	15	12	43.0	36.0	51	27	36	27	173	RED20S/15LOMD	400	315	315
S	20	16	12	45.0	36.5	55	27	36	30	182	RED20/16SOMD	420	400	400
S/L	20	18	14	43.0	35.5	51	27	36	32	178	RED20S/18LOMD	400	315	315
S	25	06	4	45.5	38.5	53	32	46	17	294	RED25/06SOMD	420	400	400
S	25	08	5	45.5	38.5	53	32	46	19	295	RED25/08SOMD	420	400	400
S	25	10	7	45.5	38.0	54	32	46	22	296	RED25/10SOMD	420	400	400
S	25	12	8	45.5	38.0	54	32	46	24	299	RED25/12SOMD	420	400	400
S	25	14	10	47.5	39.5	57	32	46	27	303	RED25/14SOMD	420	400	400
S	25	16	12	47.5	39.0	57	32	46	30	304	RED25/16SOMD	420	400	400
S/L	25	18	15	45.5	38.0	54	32	46	32	299	RED25S/18LOMD	400	315	315
S	25	20	16	49.5	39.0	61	32	46	36	315	RED25/20SOMD	420	400	400
S/L	25	22	18	47.5	40.0	56	32	46	36	304	RED25S/22LOMD	250	160	160
S	30	06	4	51.0	44.0	59	41	50	17	412	RED30/06SOMD	420	400	400
S	30	08	5	51.0	44.0	59	41	50	19	404	RED30/08SOMD	420	400	400
S	30	10	7	51.0	43.5	60	41	50	22	405	RED30/10SOMD	420	400	400
S	30	12	8	51.0	43.5	60	41	50	24	405	RED30/12SOMD	420	400	400
S	30	14	10	53.0	45.0	63	41	50	27	408	RED30/14SOMD	420	400	400
S	30	16	12	53.0	44.5	63	41	50	30	412	RED30/16SOMD	420	400	400
S	30	20	16	55.0	44.5	66	41	50	36	421	RED30/20SOMD	420	400	400

RED Tube end reducer

EO 24° DKO swivel / EO 24° cone end



Series ³⁾ ⁴⁾	D1	D2	D3	L1	L2	L3	S1	S2	S3	Weight g/1 piece	Order code*	PN (bar) ¹⁾		
												CF	A3C	71
S/L	30	22	19	53.0	45.5	61	41	50	36	406	RED30S/22LOMD	250	160	160
S	30	25	20	57.0	45.0	69	41	50	46	439	RED30/25SOMD	420	400	400
S/L	30	28	23	53.0	45.5	62	41	50	41	406	RED30S/28LOMD	250	160	160
S	38	06	4	54.5	47.5	62	50	60	17	556	RED38/06SOMD	420	315	315
S	38	08	5	54.5	47.5	62	50	60	19	581	RED38/08SOMD	420	315	315
S	38	10	7	54.5	47.0	63	50	60	22	579	RED38/10SOMD	420	315	315
S	38	12	8	54.5	47.0	63	50	60	24	577	RED38/12SOMD	420	315	315
S	38	14	10	56.5	48.5	66	50	60	27	579	RED38/14SOMD	420	315	315
S	38	16	12	56.5	48.0	66	50	60	30	580	RED38/16SOMD	420	315	315
S	38	20	16	58.5	48.0	70	50	60	36	601	RED38/20SOMD	420	315	315
S	38	25	20	60.5	48.5	73	50	60	46	615	RED38/25SOMD	420	315	315
S/L	38	28	24	56.5	49.0	65	50	60	41	573	RED38S/28LOMD	250	160	160
S	38	30	25	62.5	49.0	76	50	60	50	625	RED38/30SOMD	420	315	315
S/L	38	35	30	58.5	48.0	69	50	60	50	588	RED38S/35LOMD	250	160	160

¹⁾ Pressure shown = item deliverable

³⁾ L = light series; ⁴⁾ S = heavy series

$\frac{PN \text{ (bar)}}{10} = PN \text{ (MPa)}$

Delivery without nut and ring. Information on ordering complete fittings or alternative sealing materials see page I7.

Order code suffixes			
Material	Suffix surface and material	Example	Standard sealing material (no additional. suffix needed)
Steel, zinc plated, chrome ⁶⁾ -free	CF	RED16/12SOMDCF	NBR
Steel, zinc yellow plated	A3C	RED16/12SOMDA3C	NBR
Stainless Steel	71	RED16/12SOMD71	VIT

*Please add the **suffixes** below according to the material/surface required.