


# Filter regulator MS4-LFR-1/4-D6-CRM-AS-Z

Part number: 529145

**FESTO**



 General operating condition

## Data sheet

| Feature                                               | Value                                                                           |
|-------------------------------------------------------|---------------------------------------------------------------------------------|
| Size                                                  | 4                                                                               |
| Series                                                | MS                                                                              |
| Actuator lock                                         | Rotary knob with detent<br>can be closed with accessories                       |
| Mounting position                                     | Vertical +/- 5°                                                                 |
| Grade of filtration                                   | 5 µm                                                                            |
| Condensate drain                                      | Manually rotating                                                               |
| Design                                                | Filter regulator with pressure gauge                                            |
| Max. condensate volume                                | 19 ml                                                                           |
| Controller function                                   | Output pressure constant<br>With secondary venting<br>With return flow function |
| Bowl guard                                            | Plastic bowl guard                                                              |
| Symbol                                                | 00991589                                                                        |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | With pressure gauge                                                             |
| Operating pressure                                    | 0.08 MPa ... 1.4 MPa                                                            |
| Operating pressure                                    | 0.8 bar ... 14 bar                                                              |
| Pressure regulation range                             | 0.3 bar ... 7 bar                                                               |
| Max. pressure hysteresis                              | 0.25 bar                                                                        |
| Standard nominal flow rate                            | 1500 l/min                                                                      |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [-:4:-]<br>Inert gases                        |
| Corrosion resistance class CRC                        | 2 - Moderate corrosion stress                                                   |
| LABS (PWIS) conformity                                | VDMA24364-B1/B2-L                                                               |
| Storage temperature                                   | -10 °C ... 60 °C                                                                |
| Suitable for use with food                            | See supplementary material information                                          |
| Air purity class at output                            | Compressed air to ISO 8573-1:2010 [6:4:4]                                       |
| Media temperature                                     | -10 °C ... 60 °C                                                                |
| Ambient temperature                                   | -10 °C ... 60 °C                                                                |
| Product weight                                        | 275 g                                                                           |
| Type of mounting                                      | Either:<br>Front panel mounting<br>In-line installation<br>With accessories     |
| Pneumatic connection, port 1                          | G1/4                                                                            |
| Pneumatic connection, port 2                          | G1/4                                                                            |

| Feature                   | Value              |
|---------------------------|--------------------|
| Note on materials         | RoHS-compliant     |
| Material sub-base         | Die-cast aluminium |
| Material control panel    | PA<br>POM          |
| Material seals            | NBR                |
| Material filter           | PE                 |
| Material housing          | Die-cast aluminium |
| Material membrane         | NBR                |
| Material bowl             | PC                 |
| Material separating plate | POM                |