Reed Auto Switch Direct Mounting Type D-Z73/D-Z76/D-Z80

Grommet



Auto Switch Specifications

Refer to SMC website for the details of the products conforming to the international standards.

PLC: Programmable Logic Controller

| D-Z7 (With indicator light) | | | | | | | |
|---|---------------------------------------|-----------------------------|---------------------|--|--|--|--|
| Auto switch model | D-Z73 | | D-Z76 | | | | |
| Applicable load | Relay, PLC | | IC circuit | | | | |
| Load voltage | 24 VDC (4) | 100 VAC | 4 to 8 VDC | | | | |
| Max. load current and load current range(3) | 5 to 40 mA | 5 to 20 mA | 20 mA | | | | |
| Internal circuit* | 3 | | (5) | | | | |
| Contact protection circuit | None | | | | | | |
| Internal voltage drop | 2.4 V or less (Up to 20 mA |)/3 V or less (Up to 40 mA) | 0.8 V or less | | | | |
| Indicator light | Red LED illuminates when turned ON. | | | | | | |
| Standard | CE marking | | | | | | |
| D-Z8 (Without indicator light) | | | | | | | |
| Auto switch model | D-Z80 | | | | | | |
| Applicable load | Relay, PLC, IC circuit | | | | | | |
| Load voltage | 24 V DC or less | 48 V _{DC} | 100 V _{DC} | | | | |
| Maximum load current | 50 mA | 40 mA | 20 mA | | | | |
| Internal circuit* | 4 | | | | | | |
| Contact protection circuit | None | | | | | | |
| Internal resistance | 1 Ω or less (Including 3 m lead wire) | | | | | | |
| Standard | CE marking | | | | | | |

Oilproof Heavy-duty Lead Wire Specifications

| Chiprocally duty found this operations | | | | | | |
|--|-----------------------------------|-------------------------|----------------------------|----------------------|--|--|
| Auto switch model | | D-Z73 | D-Z76 | D-Z80 | | |
| Sheath | Outside diameter [mm] | ø2.7 | ø3.4 | ø2.7 | | |
| Insulator | Number of cores | 2 cores (Brown/Blue) | 3 cores (Brown/Blue/Black) | 2 cores (Brown/Blue) | | |
| | Outside diameter [mm] | ø1.1 | | | | |
| 0 | Effective area [mm²] | 0.18 | 0.2 | 0.18 | | |
| Conductor | Strand diameter [mm] | and diameter [mm] Ø0.08 | ø0.08 | | | |
| Lead wire minimum bendi | ng radius [mm] (Reference values) | 17 | 17 21 17 | | | |

^{*} Refer to the applicable internal circuit diagram (numbers ① to ⑦) on page 1587.

Note 2) Refer to page 1584 for lead wire lengths.

Note 3) Under 5 mA, the strength of the indicator light is poor. In some cases, visibility of the indicator light will not be possible where the output signal is less than 2.5 mA. However, there is no problem in terms of contact output, when an output signal exceeds 1 mA or

Note 4) The auto switches can operate at 12 VDC, but consider the internal voltage drop of the auto switch described in Reed Auto Switch Precautions on page 12.

Weight

(g)

| Auto swit | ch model | D-Z73 | D-Z76 | D-Z80 |
|------------------|------------------|-------|-------|-------|
| Lead wire length | 0.5 m (Nil) | 7 | 10 | 7 |
| | 3 m (L) | 31 | 55 | 31 |
| | 5 m (Z) | 50 | _ | _ |

Dimensions (mm) D-Z73, Z80 **D-Z76** M25 x 4I 27.6 Slotted set scre 2.5 Ø SMC -⊕ D-Z73 **Q 1**



Indicator light

D-Z80 without indicator light





Indicator light

Note 1) Refer to page 1584 for reed auto switch common specifications.