



Technical data

NU1008G1

Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

Visual(s)



Product definition

d	40 mm
D	68 mm
B	15 mm
E	61 mm
F	47 mm
rs min	1 mm
r1s min	0.6 mm
Radial clearance class	CN
Mass (without HJ ring)	0.22 kg
Brand	NTN

Product performance

Dynamic load, C	27.3 kN
Static load, C0	29 kN
Fatigue limit load, Cu	3.55 kN
Nlim (oil)	13,000 Tr/min
Nlim (grease)	11,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.58 Hz
Characteristic outer ring frequency, BPF0	7.83 Hz
Characteristic inner ring frequency, BPF1	10.17 Hz

Abutment dimensions

da min	44 mm
da max	46 mm
db min	49 mm
Da max	63 mm
ra max	1 mm
r1a max	0.6 mm

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$