

5 Port Pilot Operated Solenoid Valve Metal Seal, Body Ported

Series VFS3000



Model

Type of actuation		Model		Port size Rc	Flow characteristics						Max. ⁽¹⁾ operating cycle (cpm)	Response ⁽²⁾ time (ms)	Mass ⁽³⁾ (kg)
		Plug-in	Non plug-in		1→4/2(P→A/B)			4/2→5/3(A/B→R1/R2)					
					C [dm³/(s·bar)]	b	Cv	C [dm³/(s·bar)]	b	Cv			
2 position	Single	VFS3120	VFS3130	1/4	5.0	0.20	1.1	6.8	0.30	1.7	1200	20 or less	0.33
				3/8	6.1	0.14	1.4	7.3	0.23	1.8			
	Double	VFS3220	VFS3230	1/4	5.0	0.20	1.1	6.8	0.3	1.7	1500	15 or less	0.43
				3/8	6.1	0.14	1.4	7.3	0.23	1.8			
3 position	Closed center	VFS3320	VFS3330	1/4	5.0	0.20	1.1	6.3	0.27	1.6	600	40 or less	0.45
				3/8	5.7	0.20	1.4	6.8	0.21	1.7			
	Exhaust center	VFS3420	VFS3430	1/4	4.9	0.24	1.1	6.5	0.28	1.6	600	40 or less	0.45
				3/8	5.8	0.15	1.4	7.0	0.22	1.7			
	Pressure center	VFS3520	VFS3530	1/4	4.9	0.23	1.1	6.6	0.28	1.6	600	40 or less	0.45
				3/8	6.5	0.15	1.6	7.0	0.23	1.7			

Note 1) Based on JIS B 8375 (once per 30 days) for the minimum operating frequency. Note 3) In the case of grommet type.
Note 2) Based on JIS B 8375-1981. (The value at supply pressure 0.5 MPa.) Note 4) Factors of "Note 1)" and "Note 2)" are achieved in controlled clean air.

Compact yet provides a large flow capacity
3/8: C: 6.8 dm³/(s·bar)

Low power consumption:
1.8 W DC



JIS Symbol

2 position	3 position
Single	Closed center
Double	Exhaust center
	Pressure center

Standard Specifications

Valve specifications	Fluid	Air/Inert gas	
	Maximum operating pressure	1.0 MPa	
	Minimum operating pressure	0.1 MPa	
	Proof pressure	1.5 MPa	
	Ambient and fluid temperature	-10 to 60°C ⁽¹⁾	
	Lubrication	Non-lube ⁽²⁾	
	Pilot valve manual override	Non-locking push type (Flush)	
	Shock/Vibration resistance	150/50 m/s ² ⁽³⁾	
	Enclosure	Dustproof (Degrees of protection 0) ⁽⁴⁾	
	Coil rated voltage	100, 200 VAC, 50/60 Hz; 24 VDC	
Electricity specifications	Allowable voltage fluctuation	-15 to +10% of rated voltage	
	Coil insulation type	Class B or equivalent (130°C) ⁽⁵⁾	
	Apparent power (Power consumption) AC	Inrush	5.6 VA/50 Hz, 5.0 VA/60 Hz
		Holding	3.4 VA (2.1 W)/50 Hz, 2.3 VA (1.5 W)/60 Hz
	Power consumption	1.8 W (2.04 W: With light/surge voltage suppressor)	
	Electrical entry	Grommet, Grommet terminal, Conduit terminal, DIN terminal	

Note 1) Use dry air at low temperatures.
Note 2) Use turbine oil Class 1 (ISO VG32), if lubricated.
Note 3) Impact resistance: No malfunction occurred when it is tested with a drop tester in the axial direction and at the right angles to the main valve and armature in both energized and de-energized states every once for each condition. (Values at the initial period)
Vibration resistance: No malfunction occurred in a one-sweep test between 45 and 2000 Hz. Test was performed at both energized and de-energized states in the axial direction and at the right angles to the main valve and armature. (Values at the initial period)
Note 4) Based on JIS C 0920. Note 5) Based on JIS C 4003.

Option Specifications

Pilot type	External pilot ⁽¹⁾
Pilot valve manual override	Non-locking push type (Extended), Locking type (Tool required)
Coil rated voltage	110 to 120, 220, 240 VAC (50/60 Hz) 12, 100 VDC
Option	With light/surge voltage suppressor ⁽²⁾
Foot bracket (With screw)	Part no.: VFS3000-52A, VFS3120 (single) only

Note 1) Operating pressure: 0 to 1.0 MPa
Pilot pressure: 0.1 to 1.0 MPa
Note 2) Grommet type is available only w/ surge voltage suppressor (which is directly connected with lead wire), not w/ indicator light.

Manifold

Body type	Applicable manifold base	Pilot EXH
VFS3□20 VFS3□30	Stacking manifold	Individual EXH (Valve side) Common EXH (Manifold base side)

5 Port Pilot Operated Solenoid Valve Metal Seal, Body Ported **Series VFS3000**

How to Order

VFS3 **1** **20** **-** **1** **G** **-** **02** **-**

Symbol

1: 2 position single
2: position double
3: position closed center
4: position exhaust center
5: position pressure center

* Reverse pressure: Can be used by external pilot specifications.

Body (Pilot exhaust)

20: Individual EXH
30*: Common EXH

* Manifold only

Pilot type

Nil Internal pilot
R* External pilot

* Option. It will be an individual external pilot.
(External pilot port: Body side. For 30 type, common external pilot (on manifold side).)

Thread type

Nil	Rc
N*	NPT
T*	NPTF
F*	G

* Option

Port size

02	Rc 1/4
03	Rc 3/8

Manual override

Nil: Non-locking push type (Flush)
A*: Non-locking push type (Extended)
B*: Locking type (Tool required)

* Option

Light/Surge voltage suppressor

Nil	None
Z	With light/surge voltage suppressor
S*	With surge voltage suppressor

* Grommet type is available only w/ surge voltage suppressor, not w/ indicator light.

Electrical entry

G: Grommet
E: Grommet terminal
T: Conduit terminal
D, Y: DIN terminal

Coil rated voltage

1	100 VAC (50/60 Hz)
2	200 VAC (50/60 Hz)
3*	110 to 120 VAC (50/60 Hz)
4*	220 VAC (50/60 Hz)
5	24 VDC
6*	12 VDC
7*	240 VAC (50/60 Hz)
9*	Other

* Option

Option

F: With foot bracket

* Mountable only for VFS3120.

SJ
SY
SV
SYJ
SZ
VP4
S0700
VQ
VQ4
VQ5
VQC
VQZ
SQ
VFS
VFR
VQ7

How to Order Pilot Valve Assembly

SF4 **-** **1** **DZ** **-** **21**

Coil rated voltage

1	100 VAC, 50/60 Hz
2	200 VAC, 50/60 Hz
3*	110 to 120 VAC (50/60 Hz)
4*	220 VAC, 50/60 Hz
5	24 VDC
6*	12 VDC
7*	240 VAC, 50/60 Hz
9*	Other

* Option

Electrical entry, Light/Surge voltage suppressor

G	Grommet
GS	Grommet with surge voltage suppressor
D*	DIN terminal
DZ*	DIN terminal with light/surge voltage suppressor
DO*	DIN terminal **
DOZ*	DIN terminal with light/surge voltage suppressor **
Y*	DIN terminal
YZ*	DIN terminal with light/surge voltage suppressor
YO*	DIN terminal **
YOZ*	DIN terminal with light/surge voltage suppressor **
T	Conduit terminal
TZ	Conduit terminal with light/surge voltage suppressor
E	Grommet terminal
EZ	Grommet terminal with light/surge voltage suppressor

Manual override

Nil	Non-locking push type (Flush)
A*	Non-locking push type (Extended)
B*	Locking type (Tool required)
C*	Locking type (Lever)

* Option

Applicable model

14	A side pilot operator for VFS3 ₂ 20	Individual pilot exhaust
15	B side pilot operator for VFS3 ₂ 20	
16	B side pilot operator for VFS3 ₂ 20	
17	A side pilot operator for VFS3 ₃ 30	Common pilot exhaust
18	B side pilot operator for VFS3 ₃ 230	
19	B side pilot operator for VFS3 ₃ 30	

* D: Conforming to DIN43650 standard;
Y: Conforming to DIN43650B standard
** DIN connector is not attached.