


Single Shut-Off

20SFTF Plug without valve, Hose Barb


Brass



A			L	L1	D	Version
3			24	13	7	Brass
3			24	13	7	Nickel-plated brass
4			24	13	7	Brass
4			24	13	7	Nickel-plated brass
5			22	13	9	Brass
5			22	13	9	Nickel-plated brass

20SFK0 Plug without valve, with Plastic Hose Connection


Brass



A		HEX	G	L	L1	L2	Version
3 x 4		7	M7x0.5	25	7	5	Brass
3 x 4		7	M7x0.5	25	7	5	Nickel-plated brass
3 x 5		7	M7x0.5	25	7	5	Brass
3 x 5		7	M7x0.5	25	7	5	Nickel-plated brass
4 x 6		8	M8x0.5	25	7	5	Brass
4 x 6		8	M8x0.5	25	7	5	Nickel-plated brass

20SFKS Plug without valve, Panel Mount with Plastic Hose Connection

Brass




A		HEX	HEX1	B	G	L	L1	L2	Version
3 x 4		11	11	3	M7x0.5	38	7	17	Brass
3 x 4		11	11	3	M7x0.5	38	7	17	Nickel-plated brass
3 x 5		11	11	3	M7x0.5	38	7	17	Brass
3 x 5		11	11	3	M7x0.5	38	7	17	Nickel-plated brass
4 x 6		12	12	3	M8x0.5	38	7	17	Brass
4 x 6		12	12	3	M8x0.5	38	7	17	Nickel-plated brass



Single Shut-Off

20SFTS Plug without valve, Panel Mount with Hose Barb


Brass



A			HEX	HEX1	B	G	L	L1	L2	Version
3			12	11	3.5	M7x0.5	45	13	18	Brass
3			12	11	3.5	M7x0.5	45	13	18	Nickel-plated brass
4			12	11	3	M7x0.5	45	13	17	Brass
4			12	11	3	M7x0.5	45	13	17	Nickel-plated brass

20SFRP Plug without valve, Push-In

Nickel-plated brass, NBR




A		HEX	L	D
4		10	35	10



Double Shut-off

20KBA Coupler with valve, Male Thread

Brass, NBR



A			HEX	L	L1	D	Version
M5			9	26	5	10	Brass
M5			9	26	5	10	Nickel-plated brass
G1/8			11	28	7	10	Brass
G1/8			11	28	7	10	Nickel-plated brass