



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • Web site: www.timken.com

Part Number LM361649, Tapered Roller Bearings - Single Cones - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Cone Part Number	LM361649
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) ¹	437000 lbf 1940000 N
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) ²	113000 lbf 503000 N

Dimensions

12.5000 in

d - Bore	15.5000 in 392.900 mm
B - Cone Width	2.6250 in 66.675 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius³	0.330 in 8.380 mm
da - Cone Frontface Backing Diameter	14.13 in 359 mm
db - Cone Backface Backing Diameter	14.69 in 373 mm
Ab - Cage-Cone Frontface Clearance	0.25 in 6.3 mm
Aa - Cage-Cone Backface Clearance	0.14 in 3.6 mm
a - Effective Center Location⁴	0.35 in 8.9 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁵	65000 lbf 289000 N
C1 - Dynamic Radial Rating (1 million revolutions)⁶	251000 lbf 1120000 N
C0 - Static Radial Rating	497000 lbf 2210000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁷	39200 lbf 174000 N

Factors

K - Factor⁸	1.66
G1 - Heat Generation Factor (Roller-Raceway)	2730
G2 - Heat Generation Factor (Rib-Roller End)	433
Cg - Geometry Factor⁹	0.183

¹ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

² Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

³ These maximum fillet radii will be cleared by the bearing corners.

⁴ Negative value indicates effective center inside cone backface.

⁵ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁶ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁷ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ Geometry constant for Lubrication Life Adjustment Factor a_3 .

